

# AC Power Adapters (standard temp.)

*Non-locking barrel plugs, 12 VDC, 1.25 A*

Model Name	PWR-12125-WPUSJP-S1	PWR-12125-WPEU-S1	PWR-12125-WPUK-S1	PWR-12125-WPAU-S1	PWR-12125-WPCN-S1
					
<b>Input Rating</b>					
I/P	100-240 VAC 50-60 Hz	100-240 VAC 50-60 Hz	100-240 VAC 50-60 Hz	100-240 VAC 50-60 Hz	100-240 VAC 50-60 Hz
<b>Input Plug</b>					
Plug Type	US/JP	EU	UK	AU	CN
<b>Output Rating</b>					
O/P	1.25 A @ 12 VDC	1.25 A @ 12 VDC	1.25 A @ 12 VDC	1.25 A @ 12 VDC	1.25 A @ 12 VDC
<b>Output Plug</b>					
Connector Type	L-Type 5.5/2.1/9.5	L-Type 5.5/2.1/9.0	S-Type 5.5/2.1/9.0	L-Type 5.5/2.1/9.0	L-Type 5.5/2.1/9.0
Outer Diameter	5.5 ± 0.1 mm	5.5 ± 0.1 mm	5.5 ± 0.1 mm	5.5 ± 0.1 mm	5.5 ± 0.1 mm
Inner Diameter	2.1 ± 0.1 mm	2.1 ± 0.1 mm	2.1 ± 0.1 mm	2.1 ± 0.1 mm	2.1 ± 0.1 mm
<b>Physical Characteristics</b>					
Dimensions (L x W x H)	74 x 43.5 x 52.5 mm	74 x 43.5 x 73.5 mm	74 x 43.5 x 60 mm	74 x 43.5 x 52.36 mm	74 x 43.5 x 51.3 mm
Packaged Dimensions (L x W x H)	100 x 60 x 90 mm	100 x 60 x 90 mm	100 x 60 x 90 mm	100 x 60 x 90 mm	100 x 60 x 90 mm
Weight	108 g	200 g	200 g	200 g	200 g
Cord Length	1530 ± 100 mm	1800 ± 200 mm	1800 ± 200 mm	1800 ± 200 mm	1800 ± 200 mm
<b>Environmental Limits</b>					
Operating Temperature	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)
Storage Temperature	-20 to 70°C (-4 to 158°F)	-20 to 70°C (-4 to 158°F)	-20 to 70°C (-4 to 158°F)	-20 to 70°C (-4 to 158°F)	-20 to 70°C (-4 to 158°F)
<b>Regulatory Approvals</b>					
Safety	CE/FCC/UL/RCM/GS /CCC				
<b>Related Products</b>					
Related Products	NPort 5410, NPort 5430, NPort 5430I, NPort 5450, NPort 5450I, MGate MB3480				

# DC Power Cord

*Non-locking barrel plug to bare wires*

**CBL-PJTB-10**

Cable Length: 100 ± 20 mm

