




Product information Compact OpenRail Fast Ethernet Switch 4-24 ports, 1-2 fiber ports - RS20-2400S2S2SDAPHH05.0.

Industrial Ethernet:Archive - Industrial Ethernet:Compact configurable managed switches:Fast Ethernet switches:With 1-2 fiber ports:Software Release 5:Compact OpenRail Fast Ethernet Switch 4-24 ports, 1-2 fiber ports

<https://www.e-catalog.beldensolutions.com:443/link/57078-24455-49814-49854-77828-80031-85263-85264/en/RS20-2400S2S2SDAPHH05.0/uistate>

Name		Compact OpenRail Fast Ethernet Switch 4-24 ports, 1-2 fiber ports
		
		24 port Fast-Ethernet-Switch, managed, software Layer 2 Professional, for DIN rail store-and-forward-switching, fanless design
Delivery informations		
Availability	available	
Product description		
Description	24 port Fast-Ethernet-Switch, managed, software Layer 2 Professional, for DIN rail store-and-forward-switching, fanless design	
Port type and quantity	24 ports in total; 1. uplink: 100BASE-FX, SM-SC; 2. uplink: 100BASE-FX, SM-SC; 22 x standard 10/100 BASE TX, RJ45	
Type	RS20-2400S2S2SDAPHH05.0.	
Order No.	943 434-046	
New version available	Click here for the latest version	
More Interfaces		
Power supply/signaling contact	1 x plug-in terminal block, 6-pin	
V.24 interface	1 x RJ11 socket	
USB interface	1 x USB to connect the AutoConfiguration Adapter ACA21-USB	
Network size - length of cable		
Single mode fiber (SM) 9/125 µm	0 - 32,5 km, 16 dB link budget at 1300 nm, A = 0,4 dB/km, 3 dB reserve, D = 3,5 ps/(nm x km)	
Network size - cascability		
Line - / star topology	any	
Ring structure (HIPER-Ring) quantity switches	50 (reconfiguration time < 0.3 sec.)	
Power requirements		
Operating voltage	12/24/48 V DC (9,6-60) V and 24 V AC (18-30) V (redundant)	
Current consumption at 24 V DC	663 mA	
Current consumption at 48 V DC	332 mA	
Power output in Btu (IT) h	54.3	
Software		
Diagnostics	LEDs, log-file, syslog, signal contact, RMON (statistic, history, alarms, events), port mirroring, topology discovery 802.1AB, cable tester, disable learning	
Configuration	Comand Line Interface (CLI), TELNET, BootP, DHCP, DHCP Option 82, HIDiscovery, auto-configuration adapter (ACA11, ACA21-USB), watchdog Configuration, integrated DHCP server	
Security	Port Security (IP and MAC), SNMP V3, SSH, authentication (802.1x), radius authentication for SNMPv3 (web)	
Redundancy functions	HIPER-ring (ring structure), MRP (IEC-ring functionality), RSTP 802.1D-2004, redundant network/ring coupling, MRP and RSTP in parallel, redundant 24 V power supply, link aggregation	
Filter	QoS 4 classes, port prioritisation (IEEE 802.1D/p), VLAN (IEEE 802.1Q), shared VLAN learning, multicast (IGMP Snooping/Querier), multicast detection unknown multicast, broadcastlimiter, fast aging, multicast GMRP IEEE 802.1D	
Industrial Profiles	EtherNet/IP and PROFINET (2.2 PDEV, GSDML stand-alone generator, automatic device exchange) profiles included, configuration and diagnostic via automation software tools like e.g. STEP7, or Control Logix	
Time synchronisation	SNTP Server, PTP / IEEE 1588, realtime watch with energy buffer	
Flow control	Flow control 802.3x, port priority 802.1D/p, priority (TOS/DIFFSERV), prio (MAC/IP), prio mapping (TOS Layer2), traffic shaping (unicast, multicast, broadcast) ingress / egress	
Presettings	Standard	
Ambient conditions		
Operating temperature	0 °C ... 60 °C	
Storage/transport temperature	-40 °C ... 70 °C	
Relative humidity (non-condensing)	10 % ... 95 %	



Industrial Ethernet:Archive - Industrial Ethernet:Compact configurable managed switches:Fast Ethernet switches:With 1-2 fiber ports:Software Release 5:Compact OpenRail Fast Ethernet Switch 4-24 ports, 1-2 fiber ports

<https://www.e-catalog.beldensolutions.com:443/link/57078-24455-49814-49854-77828-80031-85263-85264/en/RS20-2400S2SDAPH05.0/ui/state>

MTBF	23.5 years (MIL-HDBK-217F)
Protective paint on PCB	No
Mechanical construction	
Dimensions (W x H x D)	110 mm x 131 mm x 111 mm
Mounting	DIN Rail
Weight	650 g
Protection class	IP20
Mechanical stability	
IEC 60068-2-27 shock	15 g, 11 ms duration, 18 shocks
IEC 60068-2-6 vibration	1 mm, 2 Hz-13.2 Hz, 90 min.; 0.7 g, 13.2 Hz-100 Hz, 90 min.; 3.5 mm, 3 Hz-9 Hz, 10 cycles, 1 octave/min.; 1 g, 9 Hz-150 Hz, 10 cycles, 1 octave/min
EMC interference immunity	
EN 61000-4-2 electrostatic discharge (ESD)	6 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field	10 V/m (80-1000 MHz)
EN 61000-4-4 fast transients (burst)	2 kV power line, 1 kV data line
EN 61000-4-5 surge voltage	power line: 2 kV (line/earth), 1 kV (line/line), 1 kV data line
EN 61000-4-6 conducted immunity	3 V (10 kHz-150 kHz), 10 V (150 kHz-80 MHz)
EMC emitted immunity	
FCC CFR47 Part 15	FCC 47 CFR Part 15 Class A
EN 55022	EN 55022 Class A
Approvals	
Safety of industrial control equipment	cUL 508
Hazardous locations	ISA 12.12.01 Class 1 Div. 2
Shipbuilding	n/a
Railway norm	n/a
Substation	n/a
Scope of delivery and accessories	
Scope of delivery	Device, terminal block, operating manual

For more information please contact:
Hirschmann Automation and Control GmbH
 Stuttgarter Strasse 45-51
 72654 Neckartenzlingen
 Germany
 Phone: +49 7127/14-1809
 E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.